

3.2 x 1.6 x 0.5 WiFi/Bluetooth Ceramic Chip Antenna (AA055)

1. Explanation of Product Number

H	2	U	3	4	W	G	T	Q	W	0	1	0	0
				(1)	(2)	(3)			(4)				



Product Code:

(1) Product Categories:

4: ceramic substrate chip antenna

(2) Dimensions and Polarization:

WG: 3.2x1.6x0.5(mm) / linear polarization


(3) Material / Working Frequency / Ground Plane Dimensions:

TQW: AS 6 / 2400~2500MHz / 80 x 40(mm)

(4) Antenna Series:

01: serial number



Tolerances (Unless otherwise specified) X : ± 1 X.X : ± 0.1 X.XX : ± 0.01 Angle : ± Hole Dia. : ±		 Unictron Technologies Corporation Website: www.unictron.com		
Scale :	Unit : mm	THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION		
Prepared By : Meiping	Checked By : Chinling			
Designed By : Andrew	Approved By : Herbert			
TITLE : 3.2x1.6x0.5 WiFi/Bluetooth Ceramic Chip Antenna (AA055)		DOCUMENT NO.	H2U34WGTQW0100	REV. F

2. Features

- *Stable and reliable in performances
- *Low temperature coefficient of frequency
- *Low profile, compact size
- *RoHS compliance
- *SMT processes compatible

3. Applications

- *Bluetooth earphone systems
- *Hand-held devices when Bluetooth/WiFi functions are needed, e.g., Smart phone.
- *IEEE802.11 b/g/n
- *ZigBee
- *Wireless PCMCIA cards or USB dongle

4. Description

Unictron's chip antenna series are specially designed for Bluetooth/WiFi applications. Based on Unictron's proprietary design and processes, this chip antenna has excellent stability and sensitivity to consistently provide high signal reception efficiency.


5. Electrical Specifications (80x40(mm) ground plane)

5-1.

Characteristics		Specifications	Unit
Outline Dimensions		3.2x1.6x0.5	mm
Ground Plane		80x40	mm
Center Frequency*		2442	MHz
Bandwidth (under -10dB return loss)		100 min.	MHz
VSWR		2 max.	
Impedance		50	Ω
Polarization		Linear Polarization	
Gain**	Peak	2.5 (typical)	dBi
	Efficiency	84 (typical)	%
Temperature Coefficient of Frequency		0 \pm 20 max (@ -40 $^{\circ}$ C ~85 $^{\circ}$ C)	ppm/ $^{\circ}$ C

*Center frequency will be offset to working frequency according to the conditions of user's ground plane and radome.

**The data was measured by A Test Lab Techno Corp.(CTIA Authorized Test Lab).



Tolerances (Unless otherwise specified)

X : ± 1 X.X : ± 0.1 X.XX : ± 0.01

Angle : \pm Hole Dia. : \pm

Scale : Unit : mm

Prepared By : Meiping Checked By : Chinling

Designed By : Andrew Approved By : Herbert



Unictron Technologies Corporation
Website: www.unictron.com

THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION

TITLE : 3.2x1.6x0.5 WiFi/Bluetooth Ceramic Chip Antenna (AA055)


DOCUMENT NO.

H2U34WGTQW0100


REV. F

5-2.

Return Loss(S₁₁)




VSWR



6. Antenna Dimensions & Test Board (unit: mm)


a. Antenna Dimensions




Unit : mm



Tolerances (Unless otherwise specified)	
X : ± 1	X.X : ± 0.1 X.XX : ± 0.01
Angle : ±	Hole Dia. : ±
Scale :	Unit : mm
Prepared By : Meiping	Checked By : Chinling
Designed By : Andrew	Approved By : Herbert
TITLE : 3.2x1.6x0.5 WiFi/Bluetooth Ceramic Chip Antenna (AA055)	

 Unictron Technologies Corporation Website: www.unictron.com			
		THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION	
DOCUMENT NO.	H2U34WGTQW0100	REV.	F

b. Test Board with Antenna



Unit : mm



Tolerances (Unless otherwise specified)

X : ± 1 X.X : ± 0.1 X.XX : ± 0.01

Angle : ± Hole Dia. : ±



Unictron Technologies Corporation

Website: www.unictron.com

Scale : Unit : mm

Prepared By : Meiping Checked By : Chinling

Designed By : Andrew Approved By : Herbert

THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION

TITLE : 3.2x1.6x0.5 WiFi/Bluetooth Ceramic Chip Antenna (AA055)

DOCUMENT NO.





H2U34WGTQW0100

REV.

F

7. Radiation Pattern (80x40(mm) ground plane)

7-1. 3D Gain Pattern (at 2442 MHz)



Unicon
 Technologies Corp.
 2011-07-28
 Document
 Control Center

Tolerances (Unless otherwise specified)

X : ± 1 X.X : ± 0.1 X.XX : ± 0.01

Angle : ± Hole Dia. : ±

Scale : Unit : mm

Prepared By : Meiping Checked By : Chinling

Designed By : Andrew Approved By : Herbert



Unicon Technologies Corporation
 Website: www.unicon.com

THIS SPECIFICATION IS THE PROPERTY OF UNICON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION

TITLE : 3.2x1.6x0.5 WiFi/Bluetooth Ceramic Chip Antenna (AA055)

DOCUMENT NO.

H2U34WGTQW0100


REV.

F

7-2. Efficiency Table

Frequency(MHz)	2400	2410	2420	2430	2442	2450	2460	2470	2480	2490	2500
Efficiency(dB)	-1.38	-1.04	-0.85	-0.74	-0.73	-0.76	-0.86	-1.05	-1.18	-1.27	-1.40
Efficiency(%)	72.83	78.71	82.27	84.39	84.53	84.04	82.00	78.60	76.14	74.64	72.50
Gain(dBi)	1.47	1.81	2.10	2.40	2.50	2.50	2.37	2.10	1.90	1.87	1.75

7-3. Efficiency vs. Frequency



Tolerances (Unless otherwise specified)

X : ± 1 X.X : ± 0.1 X.XX : ± 0.01

Angle : ± Hole Dia. : ±



Unictron Technologies Corporation
Website: www.unictron.com

Scale : Unit : mm

Prepared By : Meiping Checked By : Chinling

Designed By : Andrew Approved By : Herbert

THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION

TITLE : 3.2x1.6x0.5 WiFi/Bluetooth Ceramic Chip Antenna (AA055)

DOCUMENT NO.

H2U34WGTQW0100


REV.

F

8. Layout Guide:

a. Solder Land Pattern:


Land pattern for soldering (gray marking areas) is as shown below. Depending on Customer's requirement, matching circuit as shown below is also recommended .




Unit : mm

9. Frequency tuning:


a. Chip antenna tuning scenario :



Tolerances (Unless otherwise specified) X : ± 1 X.X : ± 0.1 X.XX : ± 0.01 Angle : ± Hole Dia. : ±		 Unictron Technologies Corporation Website: www.unictron.com		
Scale :	Unit : mm	THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION		
Prepared By : Meiping	Checked By : Chinling			
Designed By : Andrew	Approved By : Herbert			
TITLE : 3.2x1.6x0.5 WiFi/Bluetooth Ceramic Chip Antenna (AA055)		DOCUMENT NO.	H2U34WGTQW0100	REV. F


b. Matching circuit : (Center frequency is about 2442MHz at 80x40(mm) ground plane)

Antenna



System Matching Circuit Component		
Location	Description	Vendor
1	N/A	-
2	0Ω	(0402)
3	N/A	-
4	22pF	TDK(0402)
Fine tuning element	8pF	TDK(0402)

c. Fine tuning element vs. Center frequency



Unictron
Technologies Corp.
2011-07-28
Document
Control Center

Tolerances (Unless otherwise specified)	
X : ± 1	X.X : ± 0.1 X.XX : ± 0.01
Angle : ±	Hole Dia. : ±
Scale :	Unit : mm
Prepared By : Meiping	Checked By : Chinling
Designed By : Andrew	Approved By : Herbert
TITLE : 3.2x1.6x0.5 WiFi/Bluetooth Ceramic Chip Antenna (AA055)	

		Unictron Technologies Corporation Website: www.unictron.com	
THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION			
DOCUMENT NO.	H2U34WGTQW0100	REV.	F

10. Reliability test :

Test item	Test condition / Test method	Specification
Solderability	*Solder bath temperature : 260 ± 5°C *Immersion time : 2 ± 0.5 sec	At least 95% of a surface of each terminal electrode must be covered by fresh solder.
Resistance to dissolution of metallization)	*Solder bath temperature : 260 ± 5°C *Leaching immersion time : 30 ± 0.5 sec	Loss of metallization on the edges of each electrode shall not exceed 25%.
Drop Test	*1.8m drop on concrete with 150g weight *XYZ each 30 times	No mechanical damage. Samples shall satisfy electrical specification after test.
Bending test	Warp:2mm	No mechanical damage. Samples shall satisfy electrical specification after test.
Temperature cycle	-55°C/ 30min~125°C /30min Total 1000 cycles	No mechanical damage. Samples shall satisfy electrical specification after test
High temperature	*Temperature : 125°C *Test duration : 1000 hours	No mechanical damage. Samples shall satisfy electrical specification after test.
Low temperature	*Temperature : -55°C *Test duration : 1000 hours	No mechanical damage. Samples shall satisfy electrical specification after test.
Adhesive Strength of Termination	*Pressure:5N *Duration : 10±1 sec	No remarkable damage or removal of the termination.
Vibration	*Applied Frequency : 10-55-10Hz(1min) *1.5 p-p amplitude for XYZ each direction of 120min	No mechanical damage. Samples shall satisfy electrical specification after test
Damp heat	*Humidity:85% *Temperature:85°C *Time : 1000 hours	No mechanical damage. Samples shall satisfy electrical specification after test



Tolerances (Unless otherwise specified)

X : ± 1 X.X : ± 0.1 X.XX : ± 0.01

Angle : ± Hole Dia. : ±



Unictron Technologies Corporation
Website: www.unictron.com

Scale : Unit : mm

Prepared By : Meiping Checked By : Chinling

Designed By : Andrew Approved By : Herbert

THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION

TITLE : 3.2x1.6x0.5 WiFi/Bluetooth Ceramic Chip Antenna (AA055)

DOCUMENT NO.


H2U34WGTQW0100


REV.

F

11. Soldering Conditions:


a. Typical Soldering Profile for Lead-free Process



Tolerances (Unless otherwise specified) X : ± 1 X.X : ± 0.1 X.XX : ± 0.01 Angle : ± Hole Dia. : ±		 Unictron Technologies Corporation Website: www.unictron.com		
Scale :	Unit : mm	THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION		
Prepared By : Meiping	Checked By : Chinling			
Designed By : Andrew	Approved By : Herbert			
TITLE : 3.2x1.6x0.5 WiFi/Bluetooth Ceramic Chip Antenna (AA055)		DOCUMENT NO.	H2U34WGTQW0100	REV. F

12. Packing:

- (1) Quantity/Reel: 6000pcs/Reel
- (2) Plastic tape:



1. Cumulative tolerance of 10 sprocket hole pitch: $\pm 0.20\text{mm}$
2. Carrier camber not to exceed 1mm in 250mm
3. A_0 and B_0 measured on a plane above the inside bottom of the pocket.
4. K_0 measured from a plane on the inside bottom of the pocket to the top surface of the carrier.
5. All dimensions meet EIA-481-B requirements.
6. Material: Clear Non Anti-Static Polystyrene.
 Black Conductive Polystyrene.

2.1 Tape Dimensions(unit: mm)

Feature	Specifications	Tolerances
W	12.00	± 0.30
P	8.00	± 0.10
E	1.75	± 0.10
F	5.50	± 0.10
P2	2.00	± 0.10
D	1.50	+0.10 -0.00
Po	4.00	± 0.10
10Po	40.00	± 0.20


2.2 Pocket Dimensions(unit: mm)

Feature	Specifications	Tolerances
A_0	1.90	+0.20
B_0	3.50	-0.10
K_0	0.60	± 0.10
t	0.30	± 0.05

13. Storage Conditions:

- (1) Temperature: -25°C to 85°C
- (2) Relative Humidity: 20% to 70%



Tolerances (Unless otherwise specified) X : ± 1 X.X : ± 0.1 X.XX : ± 0.01 Angle : \pm Hole Dia. : \pm		 Unictron Technologies Corporation Website: www.unictron.com		
Scale :	Unit : mm	THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION		
Prepared By : Meiping	Checked By : Chinling			
Designed By : Andrew	Approved By : Herbert			
TITLE : 3.2x1.6x0.5 WiFi/Bluetooth Ceramic Chip Antenna (AA055)		DOCUMENT NO.	H2U34WGTQW0100	REV. F