

- * Includes Intel 80486SX running at 33 MHz.
 - * VESA local bus (VL-Bus) S3 GUI accelerator provides superior Windows and VGA performance.
 - * ZIF (Zero-Insertion-Force) socket allows easy Intel OverDrive or Pentium performance upgrades.
 - * 1 MB Video RAM standard, expandable to 2 MB.
 - * 4 MB System RAM standard, expandable to 64 MB.
 - * 8K CPU cache, expandable on-board to 1 MB write-back, direct mapped.
 - * "Fast" IDE hard drive interface with block mode support.
 - * 1.44 MB Floppy drive, with 2.88 MB FD support.
 - * Industry-standard keyboard with PS/2-style mouse.
 - * Ports:
 - 1 PS/2 keyboard
 - 1 PS/2 mouse
 - 1 parallel printer
 - 2 DB9 serial
 - * ISA Expansion slots:
 - 4 full-length
 - 3 half-length
 - * Case-mounted speaker.
 - * 3 5.25" drive bays accessible.
 - * 1 3.5" FD drive bay.
 - * 1 3.5" internal HD drive bay.
 - * 200-Watt power supply.
 - * 18.2 x 6.5 x 17.4" (H x W x D)
 - * 34 pounds.
 - * MS-DOS, OS/2, and Novell certified.
 - * Software included:
 - MS-DOS 6
 - America Online
 - Microsoft Windows 3.1
 - Microsoft Works for Windows 2.0
- > only with system that
have hard drives
installed.

