

## RS-232 TERMINAL (DB-25):

PIN NUMBER	SIGNAL
2	Transmit Data (TD)
3	Received Data (RD)
4	Request To Send (RTS)
5	Clear To Send (CTS)
6	Data Set Ready (DSR)
7	Signal Ready
8	Carrier Detect (CD)
20	Data Terminal Ready (DTR)
22	Ring Indicator (RI)
23	Rate (Rate)

## DESCRIPTION OF PIN SOCKET

PIN NUMBER	SIGNAL	PIN NUMBER	SIGNAL
A1	Not Connected	B1	GND
A2	D7	B2	BRESET
A3	D6	B3	+5V
A4	D5	B4	IRQ2
A5	D4	B5/B6	Not Connected
A6	D3	B7	-12V
A7	D2	B8	Not Connected
A8	D1	B9	+12V
A9	D0	B10	GND
A10	Not Connected	B11/B12	Not Connected
A11	AEN	B13	IOW*
A12-A21	Not Connected	B14	IOR*
A22	A9	B15-B22	Not Connected
A23	A8	B23	IRQ5
A24	A7	B24	IRQ4
A25	A6	B25	IRQ3
A26	A5	B26-B28	Not Connected
A27	A4	B29	+5V
A28	A3	B30/B31	Not Connected
A29	A2		
A30	A1		
A31	A0		

(smm 08/03/93)

□