Desk Station V PC-PA2712U

FUNCTION: To expand external interface capabilities by using Select Bay

for Modular CD-ROM/FDD, (1) 5¬" Half-height Drive Bay, (2) Full length PCI /ISA combination slots, (1) PCI Short

slot, built-in SCSI-II, and (2) Type III PC Card slots.

COMPATIBILITY: Tecra 700CS, Tecra 700CT

DIMENSIONS: OVERALL: 6.0"H x 16.2"W x 14.5"D

EXPANSION SLOTS:

Slot One $(PCI/ISA): 25.4 \times 340 \times 122mm$

 $(1.0" \times 13.39" \times 4.8")$

Slot Two (PCI/ISA): $25.4 \times 340 \times 122mm$

 $(1.0" \times 13.39" \times 4.8")$

Slot Three (PCI only): $25.4 \times 234.63 \times 122mm$

 $(1.0" \times 9.24" \times 4.8")$

PC CARD SLOTS: (2) Type III (10.5mm high)

5¬" HALF HEIGHT EXPANSION BAY:

Maximum device size: 42 x 145 x 233mm

 $(1.65"H \times 5.71"W \times 9.17"D)$

SELECT BAY (For 3«" Floppy Disk Drive or CD-ROM): Maximum device size: 17 x 128.8 x 140.6mm

 $(0.6"H \times 3.78"W \times 4.47"D)$

18.0 lbs. NOTE: Monitor stand holds 77 lbs. maximum. WEIGHT:

Stand weight: 6 lbs.

PORTS: 1 - RS232C serial port 16550 UART equiv.

1 - ECP Parallel printer port

1 - analog VGA port, 15 pin 1 - PS/2 keyboard port

1 - PS/2 mouse port

SCSI-2 port 1 -

1 -Microphone (mini-jack)

1 - Headphone (mini-jack)

1 - Line-in (mini-jack)

1 - Line-out (mini-jack)

1 - Joystick/MIDI I/F

POWER: AC INPUT: Voltage: 100-240V Frequency: 50-60Hz

> Current: 2.0A (50Hz); 1.1 (60Hz) Universal power supply (Auto-sensing)

DC OUTPUT: Continuous voltage for operation: 15 volts

Continuous current for operation: 2.7A

EXPANSION SLOTS and 57" EXPANSION BAY:

Volts DC Continuous Amps Peak Amps

+3.3V 7.0

+5V ñ5% 5.9 8.2

-5V ñ10%	0.3	_
+12V ñ5%	1.8	4.0
-12V ñ10%	0.3	_

SECURITY: 3 position key-lock (2 keys included)

50 unique security keys

Software security NoteWorthy lock slot

Additional metal lever for added security

FEATURES: Front mounted Stereo Speakers (28mm) with volume control

Auto eject button

Optimized for Windows 95 with Plug n' Play

Hot Docking Support

CRT Stand (holds 77 lbs. Maximum)

Corel SCSI Version 2 software and user manual

Docking status LED indicator VCR style docking mechanism